THOMAS BENJAMIN ARCHITECTURAL FLOORING

www.tbflooring.com - info@tbflooring.com Tel: 1-562-236-5744 -






White Oak 11003 (Premium Grade shown)

STANDARD SPECIFICATIONS

Call-out (please use this exact wording when ordering or specifying)	Thomas Benjamin White Oak 11003
Standard Plank Size	5/8" thick x 8" wide x RL to 10'
Standard Wear-Layer Thickness	4mm +/- 0.5mm
Species	American White Oak (Quercus alba)
Grade	Premium Grade (other grades available)
Core Construction	100% Select Birch Veneer - 100% exterior-grade adhesives
Finish	8 layers UV-cured urethane with ceramic hardeners
Texture	Subtly Brushed
LEED Points Available	Yes – as many as 4 LEED Points available
LEED Points Available Urea Formaldehyde Content	Yes – as many as 4 LEED Points available o% added Urea-Formaldehyde, CARBII compliant
Urea Formaldehyde Content	0% added Urea-Formaldehyde, CARBII compliant
Urea Formaldehyde Content VOC Content	0% added Urea-Formaldehyde, CARBII compliant 0% Volatile Organic Compounds
Urea Formaldehyde Content VOC Content FloorScore Certified?	o% added Urea-Formaldehyde, CARBII compliant o% Volatile Organic Compounds Yes, this product is FloorScore Certified
Urea Formaldehyde Content VOC Content FloorScore Certified? FSC Certified?	o% added Urea-Formaldehyde, CARBII compliant o% Volatile Organic Compounds Yes, this product is FloorScore Certified This product is available FSC Certified
Urea Formaldehyde Content VOC Content FloorScore Certified? FSC Certified? Structural Warranty, Light Commercial	 o% added Urea-Formaldehyde, CARBII compliant o% Volatile Organic Compounds Yes, this product is FloorScore Certified This product is available FSC Certified 10 year Limited Warranty (see complete warranty for details)

CUSTOM OPTIONS

Custom Color	Unlimited custom color options
Custom Dimensions	Options for custom plank & wear-layer thickness, widths & lengths
Custom Finish	Many alternative finish options including Akzo Ceramic, WOCA and Rubio European Oil finishes in a variety of glosses and build levels
Custom Texture	Brushing, sawmarking and a variety of hand-sculpting techniques
- Fire Treatment	Can be treated to ASTM E84 Class A / I
Pattern Options	Herringbone, chevron & parquet patterns available



Available upon request