## THOMAS BENJAMIN ARCHITECTURAL FLOORING



www.tbflooring.com - info@tbflooring.com

Tel: 1-562-236-5744 -




White Oak 11008 (Premium Grade shown)

## **STANDARD SPECIFICATIONS**

Call-out (please use this exact wording when ordering or specifying)	Thomas Benjamin White Oak 11008
Standard Plank Size	5/8" thick x 8" wide x RL to 10'
Standard Wear-Layer Thickness	4mm +/- 0.5mm
Species	American White Oak (Quercus alba)
Grade	Premium Grade (other grades available)
Core Construction	100% Select Birch Veneer - 100% exterior-grade adhesives
Finish	8 layers UV-cured urethane with ceramic hardeners
Texture	Subtly Brushed
LEED Points Available	Yes – as many as 4 LEED Points available
LEED Points Available Urea Formaldehyde Content	Yes – as many as 4 LEED Points available  o% added Urea-Formaldehyde, CARBII compliant
-	
Urea Formaldehyde Content	o% added Urea-Formaldehyde, CARBII compliant
Urea Formaldehyde Content VOC Content	o% added Urea-Formaldehyde, CARBII compliant o% Volatile Organic Compounds
Urea Formaldehyde Content  VOC Content  FloorScore Certified?	o% added Urea-Formaldehyde, CARBII compliant o% Volatile Organic Compounds Yes, this product is FloorScore Certified
Urea Formaldehyde Content  VOC Content  FloorScore Certified?  FSC Certified?	o% added Urea-Formaldehyde, CARBII compliant o% Volatile Organic Compounds Yes, this product is FloorScore Certified This product is available FSC Certified

## **CUSTOM OPTIONS**

Custom Color	Unlimited custom color options
Custom Dimensions	Options for custom plank & wear-layer thickness, widths & lengths
Custom Finish	Many alternative finish options including Akzo Ceramic, WOCA and Rubio European Oil finishes in a variety of glosses and build levels
Custom Texture	Brushing, sawmarking and a variety of hand-sculpting techniques
Fire Treatment	Can be treated to ASTM E84 Class A / I
Pattern Options	Herringbone, chevron & parquet patterns available



CERTIFIED BY SCS Global Services



The mark of responsible forestry FSC® C155330