

We will tailor the grade of your floor to suit your requirements.

In order to facilitate the grade conversation, it is helpful to start with the following:

BASIC GRADE GUIDE

Rustic Grade

Unlimited quantity filled knots to a maximum diameter of 1-1/2".

Very small cracks and pin-knots may be unfilled.

All open characteristics 1/8" and greater in diameter are filled with a 2-part catalyzed epoxy.

Very small characteristics (< 1/8") are often left unfilled in keeping with the aesthetic of the floor.

White Oak and Walnut: Sapwood may be present without limit.

Light Rustic Grade

Same characteristics as Rustic, but about half the quantity.

Approximately 1 characteristic every 2 square feet.

All open characteristics 1/8" and greater in diameter are filled with a 2-part catalyzed epoxy.

Very small characteristics (< 1/8") are often left unfilled in keeping with the aesthetic of the floor.

White Oak and Walnut: Sapwood may be present to a limited extent, primarily on the edges of some boards, not to exceed 1/3 of the width of the board.

Select Grade

Filled knots to maximum 1" diameter, filled portion not to exceed 25% of the knot size.

Sound knots to maximum 1-1/2" diameter.

Approximately 1 characteristic every 10 square feet.

All open characteristics are filled with a 2-part catalyzed epoxy.

White Oak and Walnut: Sapwood may be occasionally present, primarily on the edges of boards, not to exceed 1/8 of the width of the board.

Clear Grade

Free of knots and splits.

White Oak and Walnut: Sapwood may be occasionally present, primarily on the edges of boards, not to exceed 1/8 of the width of the board.